Scrubber/dryers BR855



Better ergonomics, better reliability, better cleaning

The BR 755/755C/855 is the generation of scrubber/dryers, with focus on performance, ergonomics and reliability.

Key features incl. an extremely low sound level, making daytime cleaning possible in sensitive areas, outstanding traction for efficient double scrubbing tasks, and excellent drying efficiency.

The new innovative Ecoflex system keeps the consumption control, but it also guarantees the possibility to boost temporarily water, detergent and brush pressure for more aggressive cleaning tasks; green meets clean.

The BR 755/755C/855 series is simply the better choice.

PRODUCT FACTS

- Ecoflex system: complete consumption control without any compromise with cleaning performance
- User friendly, waterproof one touch control panel, easy to operate and highly productive
- High manoeuvrability allows cleaning in congested areas
- Adjustable scrubbing pressure ensures better results regardless of the dirt level
- Integrated 3 stage vacuum reduces noise level to just 63dB (A)
- New squeegee concept for top drying performance
- Large battery compartment enables a 360Ah battery tray for more than 4.5 hours running time



Niffisk-Advance Australia
48 Egerton St Silverwater NSW 2128

Australia

Scrubber/dryers BR855

BR855 Model Ref. no 56601015 **NILFISK BR855** Description PRODUCT FEATURES ADJUSTABLE STEERING AND SEAT ONE TOUCH CONTROL PANEL BACK UP WARNING ALARM SAFETY INTERLOCK SWITCH **FULLY EXTERNAL SUCTION HOSE** POLYURETHANE FRONT & REAR WHEELS COMPACT SQUEEGEE CONCEPT **ECOFLEX PREPARED DEBRIS TRAY** INCL. ACCESSORIES 56601092 BLADE KIT GUM 56601086 KIT DEBRIS TRAY **NILFISK BR855** Technical specifications MAX SPEED (KM/H) 6.3 VOLTAGE (V) 24V IP PROTECTION CLASS IPX3 INSULATION CLASS Ш RATED POWER (W) 2160 BRUSH MOTOR (W) 480 VACUUM MOTOR POWER (W) 560 AIRFLOW (L/SEC) 29.7 VACUUM (KPA) 15.7 SOUND PRESSURE LEVEL (dB(A)) 63.7 SOUND PRESSURE LEVEL AT 1.5 M (DB(A)ISO 3744) 63.7 MAXIMUM RUNNING TIME 4.7 PRODUCTIVITY RATE THEORETICAL/ ACTUAL (M2/H) 5400/3800 SCRUBBING WIDTH (MM) MIN. TURN-AROUND AISLE WIDTH (CM) 171 MAX CLIMBING RATE (%) 16 WATER FLOW (L/M) 1.4/3.5 SOLUTION/RECOVERY TANK (L) 106/106 SQUEEGEE WIDTH (CM) 105 BRUSH/PAD DIAMETER (MM) 2x430 BRUSH PRESSURE (KG) 40/65/96 BRUSH SPEED (RPM) 250 BRUSH SIZE (MM) 2x430 LENGTH X WIDTH X HEIGHT (CM) 152x92x131



BATTERY COMPARTMENT SIZE (LXWXH) (MM)

GROSS WEIGHT (GVW) (KG)

NET WEIGHT (KG)

Australia

667x406x533

658

244